

Distribution - Unibundle cable B2ca (4 - 12 fibres)

UB LSZH 6XSM G657A2 SP1879 BK

Aginode Ref: 10537713

Unibundle cable up to 12 fibres

This unibundle cable is designed for indoor/outdoor installation.

This cable has an outstanding fire behaviour.

Access to the bundle is easy with the internal ripcord.

This cable can be operated under a large temperature range.

Design

The UB-B2 LSZH* SP1879 cable has a central bundle with maximum

12 fibres inside.

The design is reinforced by a layer of watertight glass yarns and a LSZH* sheath.

Fibre type


The UB-B2 LSZH* SP1879 cable is available with singlemode and multimode fibres.

Technical performances

The unibundle cable performances are specified in the following tables.

Additional details

This cable is provided as a standard with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.



STANDARDS

EN 50399 B2

IEC 60332-1

IEC 60332-3

IEC 60754-1

IEC 60794

IEC 61034

NF C32-070/C2

Euroclass

B2ca S1a a1 d0

* LSZH: Low Smoke Zero Halogen.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UB LSZH 6xSM G657A2 SP1879 BK

Eigenschaften

Konstruktionsmerkmale

| | |
|---|------------------------|
| Farbe | Schwarz |
| Fasertyp | SM (G657.A2) |
| Außenmantel | LSZH |
| Halogenfrei | IEC 60754-1 |
| Verwendetes Material für Längswasserdichtigkeit | Watertight glass yarns |
| Metallfrei | Yes |
| Leitungsaufbau | Unibundle |
| Additional strength member | Glass yarn |

Abmessungsmerkmale

| | |
|--------------------------------------|----------|
| Nettogewicht ca. | 45 kg/km |
| Anzahl der optischen Fasern | 6 |
| Anzahl der optischen Fasern, Bereich | ... |
| Außendurchmesser, nom. | 6.0 mm |

Mechanische Eigenschaften

| | |
|---------------------------------------|---------------------|
| Mechanische Festigkeit gegen Schläge | 10 impacts of 3 N.m |
| Maximalzulässige Dauerzuglast | 0.7 kN |
| Querdruckwiderstand (IEC 794-1-E3) | 200 N/cm |
| Maximale Zugspannung bei Installation | 2200 N |

Anwendungsmerkmale

| | |
|---|-------------|
| Betriebstemperatur | -40...60 °C |
| flammwidrig | IEC 60332-3 |
| Mindestbiegeradius bei statischem Einsatz | 60 mm |
| Flammwidrig | IEC 60332-1 |
| Rauchdichte | IEC 61034-2 |
| UV Beständigkeit | Very good |
| Lagertemperatur, Bereich | -40...60 °C |
| Biegeradius während Verlegung | 60 mm |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Art der Installation

Indoor/Outdoor

Umgebungstemperatur, Bereich

0...40 °C

Wasserdicht

Längs- und quer-

Erklärung zur Leistung

UB LSZH 6xSM G657A2 SP1879 BK pdf — 120.82 KB [Herunterladen](#) ↓

Verkauf & Lieferung Informationen

Standard Marking

Aginode - FIBRE OPTIC CABLE - UB-B2 LSZH B2ca s1 d0 a1 SP1879 - XXxYY - FB - TN - metric

XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number