

WallDrop V2

WALLDROP V2 12OF

Aginode Ref: 10280443

WallDrop equipped with 1 splice cassette of 12 OF

Tightness kits:

- 10 to 12mm for distribution cable
- 5 to 7mm for drop cables

The WallDrop box is designed to allow the deployment of optical cables. It is of low visual impact by its design and has the ability to distribute up to 10 secondary or subscriber cables.

It is equipped with a splice cassette for 12 splices as standard version which can be extended to 36 splices in the field without disrupting the connections (see expansion kit). The WallDrop box is used for extraction of micro-module on inline cable or is suitable for use as a transition point to feed drop cables. Metallic brackets to hold the strength member and/or aramid of cables can be provided for use as a junction box. Drop cable entries are provided with rubber seals with sealing plugs for apertures between 3 to 7mm (2 types sealing 3-5 and 5-7mm). The lateral split seals for inline cable accept cable diameters from 6 to 12mm (3 different sized seals: 6-8, 8-10 and 10-12mm).

The organiser tray consists of distinct coiling zones for fibres or micro-modules extracted from the main cable and the subscriber connection. The main cable is secured to the outside of the housing on the cable clamps.

The splice cassette has a slot for a 1x4 bare fibre splitter.

The Walldrop box can be mounted horizontally and vertically depending on the installation. It can also be installed directly suspended on the cable.

The product is supplied with all necessary accessories for the installation (combs, cassettes, seals, plastic ties and wall mounting kit).

The product is available in light grey or black.



STANDARDS

Aginode specification

WallDrop V2 120F

Eigenschaften

Konstruktionsmerkmale

Farbe	Schwarz
Werkstoff	Thermoplastic

Abmessungsmerkmale

Höhe	48 mm
Breite	138 mm
Länge	203 mm
Max. Kabelanzahl	10
Max. Kassetten Anzahl	1
Anzahl Spleiße	12
Durchmesser Hauptkabel	10...12 mm
Durchmesser Abzweigkabel	5...7 mm

Mechanische Eigenschaften

IK-Bewertung	8
--------------	---

Anwendungsmerkmale

Betriebstemperatur	-40...65 °C
Mindestbiegeradius bei statischem Einsatz	15 mm
UV Beständigkeit	Ja
Verpackung	Box
Art der Installation	Outdoor
RoHS compliant	Yes
Watertightness	IP 55

Dokumentation

Instruction manual pdf — 5.25 MB [Herunterladen](#) ↓

Leaflet Facade Solution EN pdf — 5.07 MB [Herunterladen](#) ↓

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.