

LANmark-OF Tight Buffer Universal Cca

LANMARK-OF TIGHT BUFFER UNIVERSAL 6X MULTIMODE 50/125 OM3 LSZH CCA AQUA

Aginode Ref: N165.TBUN06-AC

- Tight Buffer Universal optical fibre cable
- Indoor cable and outdoor installation in a duct
- Fully waterproof and rodent retardant
- Designed for direct termination and splicing
- 6 fibres OM3

Description and Application

The LANmark-OF Tight Buffer Universal cable is a fibre cable that can be used indoor and outdoor in a duct.

It complies with the indoor fire requirements and can be installed indoor both vertically and horizontally.

The LANmark-OF Tight Buffer Universal can also be used for outdoor installation in a duct: the water tight glass yarns make the cables fully waterproof and rodent retardant.


The LANmark-OF Tight Buffer Universal cable has 900 um buffered fibres. This second coating till 900 um provides additional protection of the fibres and facilitates the handling when terminating the fibres in a patch panel. The easy strip tight buffer design allows stripping the fibre over 10 cm in one action.

The LANmark-OF Tight Buffer Universal is most suitable for direct termination by either anaerobic or hot melt connectors. The tight buffered fibres can also be terminated with splicing of pigtails.

Tight buffer cables are available in Aqua for OM3 and OM4 and Yellow for singlemode. High exposure to UV radiation and sunlight could lead to fading of the Aqua and Yellow jacket, but the mechanical integrity of the cable jacket will be maintained.

Construction

Legend accompanying the cross section drawing:



STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

1. LSZH outer sheath with UV resistant additive
2. Watertight glass yarns
3. Optical fibres (900 um)
4. Central strength element

Characteristics

- Designed for direct termination and splicing
- Dielectric design
- Indoor cable for horizontal and vertical installations
- Fire performance compliant with IEC 60332-1, IEC 60332-3, IEC 60754-1, IEC 60794, IEC61034
- Outdoor installation in a duct
- Fully waterproof
- Rodent retardant
- UV resistant
- Available in SM, OM3 and OM4
- Available in 6-12 and 24 fibres

LANmark-OF Tight Buffer Universal 6x Multimode 50/125 OM3 LSZH Cca Aqua

Eigenschaften

Konstruktionsmerkmale

Fasertyp OM3 50/125

Abmessungsmerkmale

Nettogewicht ca. 33 kg/km

Anzahl der optischen Fasern 6

Außendurchmesser, nom. 5.3 mm

Mechanische Eigenschaften

Mechanische Festigkeit gegen Schläge 10 impacts of 3 N.m

Max. Betriebszugkraft 200 N

Max. Zugkraft (IEC 60794-1-2-E1) 700 N

Querdruckwiderstand (IEC 794-1-E3) 100 N/cm

Anwendungsmerkmale

Korrosivität der (Brand-)Gase IEC 60754-1; IEC 60754-2

Betriebstemperatur -20...70 °C

flammwidrig IEC 60332-3

Dynamischer Mindestbiegeradius während Anwendung 85.0 mm

Mindestbiegeradius bei statischem Einsatz 55 mm

Flammwidrig IEC 60332-1

Lagertemperatur, Bereich -40...70 °C

Umgebungstemperatur bei Verlegung, Bereich 0...40 °C

Erklärung zur Leistung

LANmark-OF Tight Buffer Universal 6x Multimode 50/125 OM3 LSZH Cca Aqua pdf — 141.88 KB [Herunterladen](#) ↓

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.