

10 Gigabit SFP+ Transceiver

AGINODE SFP+, 10G BASE-BX-U, 1270NM SM BI

Aginode Ref: 88646392

Aginode Small Form Factor Pluggable (SFP+) transceiver are designed for the usage in LANactive switches supporting 1 and 10 Gigabit Ethernet. Aginode SFPs are supporting several wavelength and are optimized for different dis-tances and various applications. All Aginode SFP+ modules are supporting Digital Diagnostic Monitoring (DDM) and are compliant with SFP MSA (Multi-Source Agreement) and SFF-8472. All SFPs meet Class I Laser Safety requirements in accordance with IEC-825.

- SFP+ Modules
- Class 1 Laser Safety Compliance
- Hot-swap pluggable capability
- SFP MSA specification and SFF-8472 compliant
- Wide operating temperature range, -40 to +85°C



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode SFP+, 10G Base-BX-U, 1270nm SM Bi

Characteristics

ドキュメンテーション

Detailed datasheet pdf – 275.08 KB [ダウンロード ↓](#)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.