

WallDrop V2

WINDOW PROTECTION CLIP

Aginode Ref: 13200411

- Part of the Aginode facade solution
- Protects the cable at the fibre cut point
- Accompanies WALLDROP box during the fibre extraction process
- Designed for outdoor use on facade
- Re-usable

The Window protection clip is a part of the Aginode facade solution. It accompanies the WALLDROP facade box during the fibre extraction process.

It is composed of 2 plastic parts:

- one part placed behind the facade distribution cable which supports seals and cable clamping device (plastic ties UV protected provided)
- a second part which ensures the closing of the accessory by 4 clips

The window protection clip uses the same sealing system as the WALLDROP facade box. It is therefore compatible with facade cable from 6 to 12mm (3 sets of slotted seals to cover the range: 6 to 8, 8 to 10 and 10 to 12mm). This reference integrates the seals for facade cable from 10 to 12mm (consult us for applications with different cable diameters).

It guarantees watertightness with cable opening up to 100mm.

Its protection degrees allows an outdoor use on facade (IP55 / IK07).

This accessory has the advantage to be re-enterable in case of future interventions.



STANDARDS

Aginode specification

Window protection clip

Characteristics

Construction characteristics

Colour	Black
Material	Thermoplastic

Dimensional characteristics

Height	33 mm
Width	28 mm
Length	177 mm
Max. number of cables	1
Max. number of cassettes	1
Splice number	12
Diameter main cable	10...12 mm
Diameter branch cable	3...7 mm

Mechanical characteristics

IK Rating	7
-----------	---

Usage characteristics

Operating temperature, range	-40...65 °C
Minimum static operating bending radius	15 mm
U.V resistance	Yes
Packaging	Box
Installation type	Outdoor
RoHS compliant	Yes
Watertightness	IP 55

ドキュメンテーション

Instruction manual pdf — 5.25 MB [ダウンロード ↓](#)

Leaflet Facade Solution EN pdf — 5.07 MB [ダウンロード ↓](#)