

Home networking cable Grade 3 – F/FTP - LSZH Dca

- Complies to Grade 3 standard requirements (UTE C 93-531-14)
- Guaranteed performance up to 900MHz
- Supports Gigabit Ethernet
- Suitable for CATV and cable sharing applications
- Pimf and general screening for EMC performances
- Compact design for minimum volume in ducts or trails
- Ivory printed LSZH sheath
- RoHS EC Directive compliant
- European Reach regulation compliant

Application

Aginode Grade 3 cables are the high end 900MHz offering from Aginode. Manufactured in accordance with UTE C93-531-14 requirements, this cable is the best choice to support all multimedia applications like Fast Ethernet, Gigabit Ethernet, Voice, Data, CATV,... This cable is prescribe for the new construction since July 2003 in accordance with the standard NFC 5-100 and UTE C 90-483.

Construction

- **Conductor:** Solid bare copper
- **Insulation:** Polyethylen (EN 50290-2-23) - Two insulated conductors twisted to a pair
- **Screen:** ALU/PET foil on each pair. Alu outside - 4 pairs laid up together
- **Tinned copper drain wire**
- **Screen:** ALU/PET foil - Alu inside
- **Outer sheath:** LSZH (EN 50290-2-27)

Environment

Designed to reduce the environmental impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation. The outer sheath of the cable is made of halogen free material (IEC 60754-1 / EN 50267-2-1), with limited fumes emissions (IEC 61034-1/2 / EN 50268-1/2) and no acid gaz emission in case of fire (IEC 60754-2 / EN



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

50267-2-2).

Aginode measure the environmental impact of each cable.
Upon request the PEP Ecopassport or the Eco Material
Declaration could be available.

Home networking cable Grade 3 – F/FTP - LSZH Dca

CHARACTERISTICS

구조적 특성

피복	저연 할로겐 프리
Sheath colour	아이보리 화이트
Type of cable	F/FTP
Drain wire	예
Individual screen	Aluminium / Polyester tape

치수

무게(근사치)	60 kg/km
Number of pairs	4
Conductor cross-section (AWG/KCMIL)	23
Diameter over insulation	1.45 mm
Nominal outer diameter	7.5 mm

전기적 특성

Mutual capacitance	56 nF/km
Characteristic impedance	100 Ohm
20° C에서 최대 도체 DC저항	70 Ohm/km

Transmission characteristics


Nominal Velocity of Propagation (NVP)	78 %
Propagation delay, max. 100 MHz	535 ns/100m



사용 특성

Field of application	Domestic installations
操作温度范围	-20...60 °C
Minimum static operating bending radius	30 mm
난연	NFC 32070 C2
연기밀도	Yes
Packaging	Drum 500 m
Laying operation bending radius	60 mm
Ambient installation temperature, range	0...50 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	이름	Type of cable	Packaging
	10227665	-	AGINODE F/FTP GR3 LSZH Dca 4P D500 IV	F/FTP	Drum 500 m

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.