# **Essential-6 Cable**

- Unshielded construction
- Complies to the latest Category 6 standards
- Supports Class E applications up to 250 MHz.
- Central cross maintains geometry and performance

## **Application**

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

## Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

### Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel. (Values specified at 20°C)



#### **STANDARDS**

ANSI/TIA-568-C.2 ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Page 1 / 3



# **Essential-6 Cable**

CHARACTERISTICS	
구조적 특성	
피복	폴리염화비닐
Type of cable	U/UTP
기계적 특성	
Maximum operating pulling force	100 N
사용 특성	
Range	essential-6

#### Resources

#### 문서

Freetable Ess6 channel.xls xls — 14 KB 다운로드 ±

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



Page 2/3

### **Product list**

	Aginode ref.	Country ref.	이름	피복	Type of cable
36	N100.166	-	Essential-6 U/UTP Cat 6 PVC 24AWG 305m reelex box	폴리염화비닐	U/UTP
	N100.161	-	Essential-6 U/UTP Cat 6 LSZH 24AWG 305m reelex box	저연 할로겐 프리	U/UTP
	N100.170	-	Essential-6 U/UTP Cat 6 LSZH 23AWG 305m reel in box	저연 할로겐 프리	U/UTP
35	N100.175	-	Essential-6 U/UTP Cat 6 PVC 23AWG 305m reel in box	폴리염화비닐	U/UTP
11	N100.170-GB1- D	-	Essential-6 U/UTP Cat 6 PVC 23AWG 305m reel in box	저연 할로겐 프리	U/UTP
	N100.170-GB1- D	-	Essential-6 U/UTP AWG23 CAT 6 LSZH GB 31247 B1 (d0,t0,a1) Dark Grey 305M/Reel	저연 할로겐 프리	UTP
				📞 = Make to order	, 👪 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Page 3 / 3

