WallDrop V2

WINDOW PROTECTION CLIP

Aginode Ref: 13200411

- Part of the Aginode facade solution
- Protects the cable at the fibre cut point
- Accompanies WALLDROP box during the fibre extraction process
- Designed for outdoor use on facade
- Re-usable

The Window protection clip is a part of the Aginode facade solution. It accompagnies the WALLDROP facade box during the fibre extraction process.

It is composed of 2 plastic parts:

- one part placed behind the facade distribution cable which supports seals and cable clamping device (plastic ties UV protected provided)
- a second part which ensures the closing of the accessory by 4 clips

The window protection clip uses the same sealing system as the WALLDROP facade box. It is therefore compatible with facade cable from 6 to 12mm (3 sets of slotted seals to cover the range: 6 to 8, 8 to 10 and 10 to 12mm). This reference integrates the seals for facade cable from 10 to 12mm (consult us for applications with different cable diameters).

It guarantees watertightness with cable opening up to 100mm.

Its protection degrees allows an oudoor use on facade (IP55 / IK07).

This accessory has the advantage to be re-enterable in case of future interventions.



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



Page 1 / 2

Window protection clip

Characteristics

Co	onstruction characteristics		
	Colour	Black	
	Material	Thermoplastic	
Di	mensional characteristics		
	Height	33 mm	
	Width	28 mm	
	Length	177 mm	
	Max. number of cables	1	
	Max. number of cassettes	1	
	Splice number	12	
	Diameter main cable	1012 mm	
	Diameter branch cable	37 mm	
М	echanical characteristics		
	IK Rating	7	
U	sage characteristics		
	Operating temperature, range	-4065 °C	
	Minimum static operating bending radius	15 mm	
	U.V resistance	Yes	
	Packaging	Box	
	Installation type	Outdoor	
	RoHS compliant	Yes	
	Watertightness	IP 55	

Documentation

 $Instruction\ manual\ pdf-5.25\ MB\quad \ Download\ \ \textbf{\underline{\star}}$

Leaflet Facade Solution EN pdf — 5.07 MB Download ₹

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



Page 2 / 2